arXiv:1704.04967v2 [physics.geo-ph] 18 Apr 2017

ASTROPARTICLE TECHNIQUES: COLOMBIA ACTIVE VOLCANO CANDIDATES FOR MUON TELESCOPE OBSERVATION SITES

H. Asorey[1,2], A. Balaguera-Rojas[2], L.A. Núñez[2,3], J.D. Sanabria-Gómez[2], C. Sarmiento-Cano[2], M. Súarez-Durán[2], M. Valencia-Otero[2] and A. Vesga-Ramírez[2].

We discuss a methodology to identify observation points for muongraphy of active Colombian Volcanoes and it is found that only Cerro Machín can be studied.

The MUTE (Muon Telescope) is a project to design, construct and operate a hybrid detector (2 scintillator panels + a water Cherenkov detector) to measure integrated flow of muons crossing a rock mass (≈ 100 m) in Colombian active volcanoes.

Muongraphy measures the attenuation of cosmic muon flux making it possible to build images of volcanic inner structure at the top of the edifice. It uses the same basic principles of standard medical radiography(Marteau et al. 2012; Tanaka 2014).

As the particles measured at ground are produced by the interaction of cosmic rays with atmospheric elements, its modulation needs to be carefully corrected by considering those factors that could affect the integrated flux at Earth surface –mainly geomagnetic conditions, atmospheric reaction and detector response–(Asorey et al. 2015). From this simulation chain we estimate the background muon flux, as a function of its arrival direction and energy, incident on geological structures.

Muons cross matter and lose energy described by $-\frac{dE}{d\varrho} = a(E) + b(E)E$, where $a(E)$ and $b(E)$ are functions of the material and $\varrho(L)$ the density integrated along trajectories. If we chose homogeneous standard rock, (i.e $< Z/A >= 0.5$ and density $2.65\,\mathrm{g\,cm^{-3}}$), the distances traveled by muons and its integrated flux density, –depending on their energy and arrival directions– are determined, considering volcano topographies and its surroundings, (See Figure 1).

After having analyzed four Colombian volcanoes –Nevado del Ruiz, Galeras, Cerro Machín and Cerro Negro-Chiles– we have determined that only Cerro Machín is feasible to be studied by muon tomography from two points: 4°29'39.53"N, 75°23'17.04"W, and 4°29'31.14"N, 75°22'48.31"W.



Fig. 1. Cerro Machín with ones of its raytracing



Fig. 2. Muon flux at 4°29'31.14"N, 75°22'48.31"W, Cerro Machín.

This project has been partially funded by ColCiencias, under contract FP44842-051-2015 and also supported by VIE Universidad Industrial de Santander.

REFERENCES

Asorey, H., Dasso, S., Núñez, L., Pérez, Y., Sarmiento-Cano, C., Suárez-Durán, M., & for the LAGO Collaboration. 2015, in The 34th International Cosmic Ray Conference, Vol. PoS(ICRC2015), 142

Marteau, J., Gibert, D., Lesparre, N., Nicollin, F., Noli, P., & Giacoppo, F. 2012, Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment, 695, 23

Tanaka, H. 2014, Annual Review of Earth and Planetary Sciences, 42, 535

[1]Laboratorio Detección de Partículas y Radiación, Centro Atómico Bariloche & Instituto Balseiro, Bariloche, Argentina.
[2]Escuela de Física, Universidad Industrial de Santander, Bucaramanga, Colombia.
[3]Departamento de Física, Universidad de Los Andes, Mérida, Venezuela.